


# Arrayable two-way compact trapezoid system

#### features

- Arrayable compact trapezoid enclosure
- ▶ High SPL output capability
- 70° coverage angle
- Multi-laminate birch plywood construction
- Switchable active/passive operation
- Certified MAN quick-connect flying option


### applications

- Theatre sound systems
- Club sound reinforcement
- Underslung/infill for concert sound reinforcement
- Music playback in nightclubs
- On-stage instrument monitor



It combines smooth, dynamic full frequency performance with exceptional articulation for a portable stand-alone system. Designed to meet the industry requirement for a 12" (300mm) driver plus horn configuration, Martin Audio's version is more refined for superior, professional results.

#### overall dimensions





<u>W2</u>



## technical specifications

	TYPE	Compact two-way trapezoid, switchable
		active/passive
	FREQUENCY RESPONSE (5)	$60Hz-18kHz \pm 3dB$
		-10dB @ 50Hz
	DRIVERS	12" (300mm) / 3" (75mm) voice coil
		I" (25mm) exit HF compression driver
	RATED POWER (2)	LF/(LF + HF): 300W AES, I 200W peak
		HF: 60W AES, 240W peak
	RECOMMENDED AMPLIFIER	400-550W into 4 ohms
	SENSITIVITY (6)	LF/(LF + HF): 98dB
		HF: 106dB
	MAXIMUM SPL (7)	122dB continuous, 128dB peak
	NOMINAL IMPEDANCE	LF/(LF + HF) 8 ohms
		HF: 8 ohms
	DISPERSION (-6dB)	70° horizontal, 40° vertical
	CROSSOVER	1.5kHz active/passive
	FINISH	Textured grey paint
	PROTECTIVE GRILLE	Grey perforated steel
	CONNECTORS	2 x Neutrik NL4
	FITTINGS	8 x M8
		I x mounting pole socket
		2 x MAN blanking plates
		2 x rear kelp fittings
	DIMENSIONS	(W) 365mm x (H) 554mm x (D) 364mm
		(W) 14.4ins x (H) 21.8ins x (D) 14.3ins
	WEIGHT	24kg (53lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 53312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2006 Martin Audio Ltd.

